



Main

| | |
|---------------------------|---------------------------------------------------------------------------|
| Range of product | TeSys |
| Range | TeSys |
| Device short name | DE1D |
| Product or component type | Enclosure |
| Material | Polycarbonate |
| Device composition | Thermal overload relay ordered separately Contactor ordered separately |
| Product compatibility | LE1D12 LE1D09 |
| Control type | Push-button start green I Push-button stop/reset red O |

Complementary

| | |
|--------------------|---------------------------------------------------------------------------------------------------------------------------|
| Cable entry number | 2 cable entry : ISO20 top 2 cable entry : ISO20 bottom 2 cable entry : Pg 13 bottom 2 cable entry : Pg 16 bottom |
| Height | 166 mm |
| Width | 88 mm |
| Depth | 150 mm |
| Product weight | 0.3 kg |
| Compatibility code | DE1D |

Environment

| | |
|---------------------------------------|------------------------------|
| IP degree of protection | IP65 conforming to IEC 60529 |
| IK degree of protection | IK07 conforming to IEC 60529 |
| Ambient air temperature for operation | -5...40 °C |
| Environmental characteristic | Standard environment |

Offer Sustainability

| | |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0817 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available Product environmental |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|