



Main

| | |
|---------------------------|--|
| Range of product | TeSys |
| Range | TeSys |
| Device short name | DE1D |
| Product or component type | Enclosure |
| Material | Polycarbonate |
| Device composition | Thermal overload relay ordered separately Contactor ordered separately |
| Product compatibility | LE1D12 LE1D09 |
| Control type | Selector switch 3 positions automatic start/stop/manual start I-O-II Push-button reset blue R |

Complementary

| | |
|--------------------|---|
| Cable entry number | 2 cable entry : ISO20 top 2 cable entry : ISO20 bottom 2 cable entry : Pg 13 bottom 2 cable entry : Pg 16 bottom |
| Height | 166 mm |
| Width | 88 mm |
| Depth | 165 mm |
| Product weight | 0.3 kg |
| Compatibility code | DE1D |

Environment

| | |
|---------------------------------------|------------------------------|
| IP degree of protection | IP65 conforming to IEC 60529 |
| IK degree of protection | IK07 conforming to IEC 60529 |
| Ambient air temperature for operation | -5...40 °C |
| Environmental characteristic | Standard environment |

Offer Sustainability

| | |
|------------------------|---|
| RoHS (date code: YYWW) | Compliant - since 1640 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
|------------------------|---|

REACH

Reference not containing SVHC above the threshold

Reference not containing SVHC above the threshold
