Product data sheet Characteristics

DE1DS2A04

TeSys LE - enclosure for DOL starter - without pushbuttons





Main

Range of product	TeSys	
Range	TeSys	
Device short name	DE1D	
Product or component type	Enclosure	
Material	Polycarbonate	
Device composition	Thermal overload relay ordered separately Contactor ordered separately	
Product compatibility	LE1D1835	
Control type	Without	

Complementary

Cable entry number	2 cable entry: ISO20 top 2 cable entry: ISO20 bottom 2 cable entry: Pg 16 bottom 2 cable entry: ISO25 top 2 cable entry: Pg 21 bottom 2 cable entry: ISO25 bottom	
Height	201 mm	
Width	103 mm	:
Depth	145 mm	
Product weight	0.5 kg	
Compatibility code	DE1D	

Environment

IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 60529
Ambient air temperature for operation	-540 °C
Environmental characteristic	Standard environment

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0840 - Schneider Electric declaration of conformity
	Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months