



## Main

Range of product	TeSys fuse-disconnector
Range	TeSys
Product name	TeSys DF
Product or component type	Fuse-disconnector
Device short name	DF22
Poles description	3P

## Complementary

Product compatibility	Fuse cartridge striker
Mounting support	Rail
Mounting position	Vertical +/- 23°
Control type	Toggle
[Ie] rated operational current	125 A for power circuit
[Uimp] rated impulse withstand voltage	8 kV
Fire resistance	960 °C conforming to IEC 60695-2-1
[Ipk] rated peak withstand current	19 kA with tubular links conforming to IEC 60269-1
Short-circuit withstand	120 kA 400 V conforming to IEC 60947-3 120 kA 500 V conforming to IEC 60947-3 80 kA 690 V conforming to IEC 60947-3
Fuse size	22 x 58 mm
Fuse type	AM GG
[Ui] rated insulation voltage	690 V for power circuit AC 690 V for power circuit DC
Connections - terminals	1 solid cable(s) 2.5...35 mm <sup>2</sup> on screw clamp terminals for power circuit 2 solid cable(s) 2.5...25 mm <sup>2</sup> on screw clamp terminals for power circuit 1 flexible cable(s) 2.5...35 mm <sup>2</sup> without cable end on screw clamp terminals for power circuit 2 flexible cable(s) 2.5...25 mm <sup>2</sup> without cable end on screw clamp terminals for power circuit 1 flexible cable(s) 2.5...35 mm <sup>2</sup> with cable end on screw clamp terminals for power circuit 2 flexible cable(s) 2.5...25 mm <sup>2</sup> with cable end on screw clamp terminals for power circuit
Tightening torque	4 N.m power circuit : on screw clamp terminals
Quantity per set	Set of 2
Compatibility code	DF22

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environment

Standards	IEC 60947-3 CSA C22.2 No 39 UL 512
Product certifications	UR
IP degree of protection	IP20 conforming to IEC 60529
Protective treatment	TH
Ambient air temperature for storage	-40...80 °C
Ambient air temperature for operation	-20...60 °C with derating
Height	127.5 mm
Width	105 mm
Depth	76.5 mm
Product weight	0.657 kg

## Contractual warranty

Warranty period	18 months
-----------------	-----------