



## Main

|                           |  |
|---------------------------|--|
| Range of product          | Digilink   |
| Product or component type | Fibre optic cable single mode  |
| Optic fibre type          | Light armoured for outdoor - duct, aerial, direct buried application |

## Complementary

|                       |                       |
|-----------------------|-----------------------|
| Optic fiber core      | 9 µm                  |
| Condition of use      | Outdoor               |
| Cable weight          | 90 kg/km              |
| Bending radius        | 20 x overall diameter |
| Number of optic fibre | 4                     |
| Pulling force         | 1000 N                |
| Crush resistance      | 0.044 N/m             |

## Environment

|                                       |                                |
|---------------------------------------|--------------------------------|
| Ambient air temperature for operation | -30...70 °C                    |
| Ambient air temperature for storage   | -40...75 °C                    |
| Standards                             | TIA/EIA-568-B<br>ISO/IEC 11801 |

## Offer Sustainability

|                        |   |
|------------------------|---|
| RoHS (date code: YYWW) | Compliant - since 1736 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
|------------------------|---|

## Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

# DFXAO09GCT04