



Main

Range	TeSys
Product name	TeSys DPE
Product or component type	Contactor
Device short name	DPE
Device application	Control
Contactor application	Motor control Non-reversing
Quantity per set	Set of 1

Complementary

Utilisation category	AC-1 AC-3 AC-4
Poles description	3P
Pole contact composition	3 NO
[Ue] rated operational voltage	690 V AC 50/60 Hz at power circuit
[Ie] rated operational current	38 A AC supply utilisation category AC-1 for power circuit at 690 V 38 A AC supply utilisation category AC-3 for power circuit at 690 V 38 A AC supply utilisation category AC-4 for power circuit at 690 V
Motor power kW	9 kW 230 V AC at 50/60 Hz
Control circuit type	AC standard, frequency : 50/60 Hz
[Uc] control circuit voltage	24 V AC 50/60 Hz
Auxiliary contact composition	Without
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947-4-1 6 kV conforming to EN 60947-1 6 kV conforming to IEC 60947-1
Overvoltage category	III
[Ith] conventional free air thermal current	50 A ambient air temperature 60 °C at power circuit
Irms rated making capacity	550 A 440 V AC at power circuit conforming to IEC 60947
Rated breaking capacity	550 kA 440 V at power circuit conforming to IEC 60947
Associated fuse rating	63 A curve gG at <= 690 V coordination type 1 conforming to IEC 60947 63 A curve gG at <= 690 V coordination type 2 conforming to IEC 60947
Average impedance	2 mOhm, frequency : 50 Hz at 63 A-power circuit

[Ui] rated insulation voltage	690 V conforming to IEC 60947-4-1
Electrical durability	800000 cycles
Power dissipation per pole	3 W utilisation category AC-3 5 W utilisation category AC-1
Mounting support	DIN rail Plate
Connections - terminals	Screw clamp terminals control circuit 2 1...2.5 mm ² flexible with cable end Screw clamp terminals power circuit 1 1...4 mm ² flexible with cable end Screw clamp terminals power circuit 2 1...2.5 mm ² flexible with cable end Screw clamp terminals power circuit 1 1...4 mm ² solid without cable end Screw clamp terminals power circuit 2 1...4 mm ² solid without cable end Screw clamp terminals control circuit 1 1...4 mm ² flexible without cable end Screw clamp terminals control circuit 2 1...4 mm ² flexible without cable end Screw clamp terminals control circuit 1 1...4 mm ² flexible with cable end Screw clamp terminals control circuit 1 1...4 mm ² solid without cable end Screw clamp terminals control circuit 2 1...4 mm ² solid without cable end
Tightening torque	2.5 N.m for screw terminals at power circuit 2.5 N.m for screw terminals at control circuit
Operating time	12...22 ms on closing 4...19 ms on opening
Mechanical durability	30000000 cycles
Control circuit voltage limits	0.85...1.1 U _{ambient air temperature} ≤ 60 °C at operational at 50/60 Hz 0.8...1.1 U _{ambient air temperature} ≤ 50 °C at operational at 50/60 Hz 0.3...0.6 U _{ambient air temperature} ≤ 60 °C at drop-out at 50/60 Hz
Inrush power in VA	70 VA _{ambient air temperature} 20 °C (cos phi = 0.75) at 50 Hz 70 VA _{ambient air temperature} 20 °C (cos phi = 0.75) at 60 Hz
Hold-in power consumption in VA	7 VA _{ambient air temperature} 20 °C (cos phi = 0.3) at 50 Hz 7.5 VA _{ambient air temperature} 20 °C (cos phi = 0.3) at 60 Hz
Mechanical robustness	Vibrations at contactor open for 2 Gn, 5...300 Hz Vibrations at contactor closed for 4 Gn, 5...300 Hz Shocks at 11 ms at contactor closed for 15 gn Shocks at 11 ms at contactor open for 8 gn
Height	85 mm
Width	45 mm
Depth	90 mm
Product weight	0.32 kg

Environment

Standards	EN 60947-1 EN 60947-4-1 IEC 60947-1 IEC 60947-4-1
Product certifications	CSA UL
Heat dissipation	2...3 W
IP degree of protection	IP2x IEC 60947
Pollution degree	3
Protective treatment	TH conforming to IEC 60068
Ambient air temperature for storage	-60...80 °C
Permissible ambient air temperature around the device	-40...70 °C at U _c
Operating altitude	3000 m-without derating
Fire resistance	960 °C conforming to IEC 60695-2-1