



Main

| | |
|---------------------------|-----------------------|
| Range of product | Neo C-Metro |
| Product or component type | Fused connection unit |
| Switch function | 1-pole |
| Colour tint | White |
| Standards | BS 5733 |

Complementary

| | |
|-------------------------|--|
| Wiring device mounting | Flush Surface |
| Rated current | 5 A, 250 V, AC, 50 Hz |
| Contacts material | Phosphor bronze Brass |
| Load type | Resistive |
| Protection type | Fuse |
| Material | Polycarbonate with grid plate Polycarbonate with surround |
| Number of cables | 2 - cable cross section: 4 mm ² with input 1 - cable cross section: 1.5 mm ² with output 1 - cable cross section: 2.5 mm ² with output 3 - cable cross section: 0.5...1.5 mm ² with output 3 - cable cross section: 2.5 mm ² with input |
| Connections - terminals | Pillar terminals |
| Width | 87 mm |
| Height | 87 mm |
| Depth | 8 mm |

Environment

| | |
|---------------------------------------|------------|
| Ambient air temperature for operation | 0...40 °C |
| Relative humidity | 0...95 % |
| Environmental characteristic | Indoor use |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|