



Main

Range of product	Modicon LMC078
Product or component type	Motion controller
Product specific application	Packaging Material working Material handling
Discrete I/O number	20
Battery type	3 V lithium battery

Complementary

Discrete input number	12 total input 8 regular input 4 capture input
Discrete input logic	Sink
Discrete input voltage	24 V
Discrete input voltage type	DC
Voltage state 1 guaranteed	15...30 V input
Voltage state 0 guaranteed	-3...5 V input
Discrete input current	4 mA
Input impedance	6 kOhm
Configurable filtering time	0.1...4290 ms regular input 0.1...4290 ms capture input
Discrete output number	8 output
Discrete output logic	Source
Discrete output voltage	24 V DC
Output voltage limits	19.2...28.8 V
Protection type	Short-circuit protection
Input/Output number	<= 768 distributed for discrete inputs and outputs <= 364 distributed for analog inputs and outputs
[Us] rated supply voltage	24 V DC
Supply voltage limits	20.4...30 V
[In] rated current	500 mA per output < 2 A for all outputs
Peak current	<= 2 A (duration= 1 s)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Execution time per instruction	2 ns
Memory type	128 MB NVRAM memory 512 MB RAM memory
Data storage equipment	512 MB SD card
Programming language	CFC (continuous function chart) FBD (function block diagram) IL (instruction list) LD (ladder) SFC (sequential function chart) ST (structured text)
Realtime clock	With +/- 1 s/day
Data backed up	Variables of type retain and retain persistent with battery Date and hour with battery
Battery life	10 yr
Integrated connection type	1 CAN port with male SUB-D 9 connector; protocol: CANopen with master method 1 isolated serial link with mini B USB connector; transmission rate: 480 Mbit/s 1 encoder with screw terminal block connector 1 isolated serial link with female RJ45 connector; physical interface: SERCOS III 1 isolated serial link with female RJ45 connector; protocol: Ethernet Modbus TCP/IP with slave method; physical interface: 10BASE-T/100BASE-TX; transmission rate: 300...115200 bps 1 isolated serial link with female RJ45 connector; protocol: Modbus with master/slave method; transmission frame: RTU/ASCII or character mode ASCII; physical interface: RS232/RS485; transmission rate: 480 Mbit/s 1 isolated serial link with USB type A connector
Local signalling	1 LED green with PRG marking for programming indication 1 LED green, orange and red with SIII marking for SERCOS III bus status 1 LED green/red with STS marking for status of the module (Mod Status) 1 LED green/red with CAN marking for CANopen bus status
Marking	CE
Mounting support	Screw clamp
Width	45 mm
Height	230 mm
Depth	220 mm
Product weight	2.2 kg

Environment

Standards	CSA C22.2 No 142 UL 508
Product certifications	CSA UL
Ambient air temperature for operation	5...55 °C vertical installation
Ambient air temperature for storage	-25...70 °C
Relative humidity	5...95 % without condensation
IP degree of protection	IP20 conforming to IEC 61131-2
Pollution degree	2
Operating altitude	0...2000 m without derating
Storage altitude	0...3000 m
Vibration resistance	10 m/s ²
Shock resistance	100 m/s ²

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1429 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental

E3031DFSG_GS