



Main

| | |
|------------------------|---|
| Range of product | Neo C-Metro |
| Wiring device mounting | Surface Flush |
| Switch function | 1-way |
| Switch application | Switch |
| Load type | Inductive Incandescent lamp Resistive Fluorescent lamp |
| Bulb type | Fluorescent with green |
| Colour tint | Grey silver |

Complementary

| | |
|------------------------------|--|
| Rated current | 10 A, 250 V, AC, 50/60 Hz |
| Number of gangs | 1 gang horizontal |
| Material | Brass metal parts Polycarbonate plastic part Steel metal parts |
| Clamping connection capacity | 3 x 2.5 mm ² for solid cable(s) 3 x 2.5 mm ² for stranded cable(s) 4 x 1.5 mm ² for solid cable(s) 4 x 1.5 mm ² for stranded cable(s) |
| Connections - terminals | Pillar terminals |
| Width | 87 mm |
| Height | 87 mm |
| Embedding depth | 23.5 mm |
| Depth | 36 mm |

Environment

| | |
|---------------------------------------|---------------------------|
| Ambient air temperature for operation | 0...40 °C |
| Relative humidity | 0...95 % |
| Environmental characteristic | Indoor use |
| Standards | GB 16915.1 IEC 60669-1 |

Offer Sustainability

RoHS (date code: YYWW)

Compliant - since 0841 - Schneider Electric declaration of conformity

 [Schneider Electric declaration of conformity](#)

Contractual warranty

Warranty period

18 months
