



### Main

Range of product	Neo C-Metro
Wiring device mounting	Flush Surface
Switch function	Momentary
Switch application	Bell
Load type	Resistive
Bulb type	Fluorescent with green
Colour tint	Grey silver

### Complementary

Rated current	4 A, 250 V, AC, 50/60 Hz
Number of gangs	1 gang horizontal
Material	Polycarbonate plastic part
Clamping connection capacity	3 x 2.5 mm <sup>2</sup> for solid cable(s) 3 x 2.5 mm <sup>2</sup> for stranded cable(s) 4 x 1.5 mm <sup>2</sup> for solid cable(s) 4 x 1.5 mm <sup>2</sup> for stranded cable(s)
Connections - terminals	Pillar terminals
Width	87 mm
Height	87 mm
Embedding depth	23 mm
Depth	36 mm

### Environment

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use
Standards	GB 16915.1 IEC 60669-1 EN 60669-1

E3031HBP\_GS

Offer Sustainability

---

RoHS (date code: YYWW)	Compliant - since 0841 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
------------------------	---

---

Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---