



Main

Range of product	Neo C-Metro
Wiring device mounting	Surface Flush
Switch function	2-pole
Switch application	Switch
Load type	Inductive Fluorescent lamp Resistive
Bulb type	LED with white
Colour tint	White

Complementary

Rated current	20 AX, 250 V, AC, 50 Hz
Number of gangs	1 gang horizontal
Material	Brass metal parts Polycarbonate plastic part Steel metal parts
Clamping connection capacity	1 x 2.5...1 x 6 mm ² for solid cable(s) 1 x 2.5...1 x 6 mm ² for stranded cable(s)
Connections - terminals	Pillar terminals
Width	87 mm
Height	87 mm
Embedding depth	19.7 mm
Depth	33.1 mm

Environment

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use
Standards	IEC 60669-1 EN 60669-1 GB 16915.1

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0841 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
------------------------	---

Contractual warranty

Warranty period	18 months
-----------------	-----------
