



Main

Range of product	Neo C-Metro
Wiring device mounting	Flush Surface
Switch function	Intermediate
Switch application	Switch
Load type	Fluorescent lamp Inductive Resistive
Bulb type	LED with white
Colour tint	White

Complementary

Rated current	16 AX, 250 V, AC, 50 Hz 20 A, 250 V, AC, 50 Hz
Number of gangs	1 gang horizontal
Material	Brass metal parts Polycarbonate plastic part
Clamping connection capacity	3 x 2.5 mm ² for solid cable(s) 3 x 2.5 mm ² for stranded cable(s) 4 x 1.5 mm ² for solid cable(s) 4 x 1.5 mm ² for stranded cable(s)
Connections - terminals	Pillar terminals
Width	87 mm
Height	87 mm
Embedding depth	23.5 mm
Depth	36 mm

Environment

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use
Standards	IEC 60669-1 MS 616 SS 227

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0841 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
------------------------	---

Contractual warranty

Warranty period	18 months
-----------------	-----------
