



Main

| | |
|---------------------------|---|
| Range of product | Neo C-Metro |
| Product or component type | Control switch |
| Wiring device mounting | Flush Surface |
| Switch function | 1-way |
| Switch application | Switch |
| Load type | Resistive Fluorescent lamp Incandescent lamp Inductive |
| Colour tint | White |

Complementary

| | |
|------------------------------|--|
| Rated current | 10 AX, 250 V, AC, 50/60 Hz |
| Number of gangs | 1 gang horizontal |
| Material | Polycarbonate plastic part |
| Clamping connection capacity | 3 x 2.5 mm ² for solid cable(s) 3 x 2.5 mm ² for stranded cable(s) 4 x 1.5 mm ² for solid cable(s) 4 x 1.5 mm ² for stranded cable(s) |
| Connections - terminals | Pillar terminals |
| Width | 87 mm |
| Height | 87 mm |
| Embedding depth | 24.2 mm |
| Depth | 37.3 mm |

Environment

| | |
|---------------------------------------|---|
| Ambient air temperature for operation | 0...40 °C |
| Relative humidity | 0...95 % |
| Environmental characteristic | Indoor use |
| Standards | IEC 60669-1 GB 16915.1 EN 60669-1 |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|
