

Product data sheet  
Characteristics

# E3031V2\_EWWW

1 Gang 2 Way Vertical Dolly Switch with White LED, White



## Main

Range of product	Neo C-Metro
Wiring device mounting	Flush Surface
Switch function	2-way
Switch application	Switch
Load type	Fluorescent lamp Inductive Resistive Incandescent lamp
Bulb type	LED with white
Colour tint	White

## Complementary

Rated current	10 AX, 250 V, AC, 50/60 Hz
Number of gangs	1 gang vertical
Material	Brass metal parts Polycarbonate plastic part Steel metal parts
Clamping connection capacity	3 x 2.5 mm <sup>2</sup> for solid cable(s) 3 x 2.5 mm <sup>2</sup> for stranded cable(s) 4 x 1.5 mm <sup>2</sup> for solid cable(s) 4 x 1.5 mm <sup>2</sup> for stranded cable(s)
Connections - terminals	Pillar terminals
Width	87 mm
Height	87 mm
Embedding depth	23.5 mm
Depth	36 mm

## Environment

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use
Standards	IEC 60669-1 GB 16915.1

### Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1642 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>

---

### Contractual warranty

Warranty period	18 months
-----------------	-----------

---