



Main

Range of product	Neo C-Metro
Product or component type	Control switch
Wiring device mounting	Flush Surface
Switch function	Momentary
Switch application	Bell
Load type	Inductive Resistive
Colour tint	Grey silver

Complementary

Rated current	4 A, 250 V, AC, 50/60 Hz
Number of gangs	1 gang vertical
Material	Polycarbonate plastic part
Clamping connection capacity	3 x 2.5 mm ² for solid cable(s) 3 x 2.5 mm ² for stranded cable(s) 4 x 1.5 mm ² for solid cable(s) 4 x 1.5 mm ² for stranded cable(s)
Connections - terminals	Pillar terminals
Width	87 mm
Height	87 mm
Embedding depth	23 mm
Depth	36 mm

Environment

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use
Standards	GB 16915.1 EN 60669-1 IEC 60669-1

E3031VBPD_GS

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1642 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------
