



### Main

Range of product	Neo C-Metro
Product or component type	Control switch
Wiring device mounting	Flush Surface
Switch function	2-way
Switch application	Switch
Load type	Resistive Inductive Fluorescent lamp Incandescent lamp
Bulb type	LED with white
Colour tint	White

### Complementary

Rated current	10 A, 250 V, AC, 50/60 Hz
Number of gangs	2 gangs horizontal
Material	Brass metal parts Polycarbonate plastic part Steel metal parts
Clamping connection capacity	3 x 2.5 mm <sup>2</sup> for solid cable(s) 3 x 2.5 mm <sup>2</sup> for stranded cable(s) 4 x 1.5 mm <sup>2</sup> for solid cable(s) 4 x 1.5 mm <sup>2</sup> for stranded cable(s)
Connections - terminals	Pillar terminals
Width	87 mm
Height	87 mm
Embedding depth	23.5 mm
Depth	36 mm

### Environment

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use
Standards	GB 16915.1

### Offer Sustainability

RoHS (date code: YYWW)

Compliant - since 0841 - Schneider Electric declaration of conformity

 [Schneider Electric declaration of conformity](#)

---

### Contractual warranty

Warranty period

18 months

---