



### Main

Range of product	Neo C-Metro
Product or component type	Control switch
Wiring device mounting	Surface Flush
Switch function	2-pole
Switch application	Switch
Load type	Incandescent lamp Resistive Inductive
Bulb type	LED with white
Colour tint	White

### Complementary

Rated current	20 A, 250 V, AC, 50 Hz
Number of gangs	2 gangs horizontal
Material	Brass metal parts Polycarbonate plastic part
Clamping connection capacity	1 x 4 mm <sup>2</sup> for stranded cable(s) 1 x 4 mm <sup>2</sup> for solid cable(s) 1 x 6 mm <sup>2</sup> for solid cable(s) 1 x 6 mm <sup>2</sup> for stranded cable(s) 4 x 2.5 mm <sup>2</sup> for solid cable(s) 4 x 2.5 mm <sup>2</sup> for stranded cable(s)
Connections - terminals	Pillar terminals
Width	87 mm
Height	87 mm
Embedding depth	21.5 mm
Depth	38.1 mm

### Environment

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use
Standards	IEC 60669-1

## Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---