



Main

Range of product	Neo C-Metro
Range	Neo C-Metro
Product or component type	Dimmer
Bulb type	LED blue
Number of gangs	2 gangs
Colour tint	Grey silver

Complementary

Wiring device mounting	Surface Flush
Power range	40...400 VA 2 incandescent lamp 40...400 VA 2 low voltage halogen lamp with electronic transformer
[Ue] rated operational voltage	220...240 V AC 50/60 Hz
Material	Brass metal parts Polycarbonate plastic part Steel metal parts
Clamping connection capacity	3 x 2.5 mm ² for solid cable(s) 3 x 2.5 mm ² for stranded cable(s) 1 x 4 mm ² for stranded cable(s) 2 x 4 mm ² for stranded cable(s) 1 x 2.5 mm ² for solid cable(s) 1 x 2.5 mm ² for stranded cable(s) 2 x 2.5 mm ² for solid cable(s) 2 x 2.5 mm ² for stranded cable(s)
Connections - terminals	Pillar terminals
Width	87 mm
Height	87 mm
Depth	26 mm

Environment

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use
Standards	IEC 60669-2-1

Contractual warranty

Warranty period	18 months
-----------------	-----------
