

# Product data sheet

## Characteristics

# E3032V1\_FGGS

## 2 Gang 1 Way Vertical Dolly with Green Fluorescent Indicator, Grey Silver



### Main

Range of product	Neo C-Metro
Product or component type	Control switch
Wiring device mounting	Flush Surface
Switch function	1-way
Switch application	Switch
Load type	Inductive Resistive Fluorescent lamp Incandescent lamp
Bulb type	Fluorescent with green
Colour tint	Grey silver

### Complementary

Rated current	10 AX, 250 V, AC, 50/60 Hz
Number of gangs	2 gangs vertical
Material	Brass metal parts Polycarbonate plastic part Steel metal parts
Clamping connection capacity	3 x 2.5 mm <sup>2</sup> for solid cable(s) 3 x 2.5 mm <sup>2</sup> for stranded cable(s) 4 x 1.5 mm <sup>2</sup> for solid cable(s) 4 x 1.5 mm <sup>2</sup> for stranded cable(s)
Connections - terminals	Pillar terminals
Width	87 mm
Height	87 mm
Embedding depth	23.5 mm
Depth	36 mm

### Environment

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use
Standards	EN 60669-1

## Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0850 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>

---

## Contractual warranty

Warranty period	18 months
-----------------	-----------

---