



Main

Range of product	Neo C-Metro
Product or component type	Control switch
Wiring device mounting	Flush Surface
Switch function	2-way
Switch application	Switch
Load type	Resistive Fluorescent lamp Inductive Incandescent lamp
Bulb type	Fluorescent with white
Colour tint	White

Complementary

Rated current	10 AX, 250 V, AC, 50/60 Hz
Number of gangs	2 gangs vertical
Material	Brass metal parts Polycarbonate plastic part Steel metal parts
Clamping connection capacity	3 x 2.5 mm ² for solid cable(s) 3 x 2.5 mm ² for stranded cable(s) 4 x 1.5 mm ² for solid cable(s) 4 x 1.5 mm ² for stranded cable(s)
Connections - terminals	Pillar terminals
Width	87 mm
Height	87 mm
Embedding depth	23.5 mm
Depth	36 mm

Environment

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use
Standards	IEC 60669-1

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1642 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------
