Product data sheet Characteristics

E3426-10IS_GS

TruGlobal Socket (only available in selected countries), Grey Silver



Main

| TTTOTT | | 2. |
|----------------------------|--------------------------------------|---------------|
| Range of product | Neo C-Metro | † |
| Product or component type | Power socket-outlet | 2 |
| Outlet poles configuration | 2P with shutters 3P with shutters | ي ا |
| Outlet standard | IEC 60884 | ن <u>ئ</u> |
| Colour tint | Grey silver | |

Complementary

| Complementary | | |
|-------------------------|---------------------------------|--|
| Wiring device mounting | Flush |). !! |
| | Surface | ella Hili |
| Rated current | 10 A, 250 V, AC, 50/60 Hz | |
| Material | Brass with metal parts | <u> </u> |
| | Polycarbonate with plastic part | ###################################### |
| | Steel with metal parts | |
| Load type | Resistive | |
| Connections - terminals | Pillar terminals | ģ |
| Width | 87 mm | |
| Height | 87 mm | |
| Depth | 23 mm | |
| | | |

Environment

| | | Φ |
|---------------------------------------|------------|--------|
| Ambient air temperature for operation | 040 °C | stitut |
| Relative humidity | 095 % | a sub |
| Environmental characteristic | Indoor use | as |

Contractual warranty

| Warranty period 18 | months |
|--------------------|--------|
|--------------------|--------|

E3426-10IS_GS