

# Product data sheet

## Characteristics

# E3854D1L2EA\_GB

2 Gang, Leading Edge Dimmer, 2 x 250VA,  
434MHz, Grey Silver



### Main

Range of product	Neo-X
Product or component type	Dimmer
Transmission frequency	434 MHz
Power range	25...250 VA incandescent lamp per channel 25...250 VA low voltage halogen lamp with transformer per channel
Number of gangs	2 gangs
Provided equipment	Screws User manual
Colour tint	Grey silver

### Complementary

[Ue] rated operational voltage	220...240 V AC 50 Hz
Status LED	LED backlight blue bright lights on LED backlight blue dim lights off LED backlight blue flash clear mode LED backlight blue flash program mode LED backlight blue off lights off while other channels still on Program LED red flash full memory Program LED red off control mode Program LED red on clear mode Program LED red on program mode
Distance between centers	60.3 mm
Width	87 mm
Height	87 mm
Depth	36 mm

### Environment

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Standards	EN 60669-2-1 ETSI EN 300 220-1 ETSI EN 300 220-2

E3854D1L2EA\_GB

Offer Sustainability

---

RoHS (date code: YYWW)	Will be compliant on 4Q2016
	Will be compliant on 4Q2016

---

Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---