



Main

Range of product	Pieno
Product or component type	Power socket-outlet
Switch function	Switch
Rated current	10 A, 250 V, , AC, 50 Hz
Local signalling	Neon amber
Number of gangs	1 gang
Load type	No inductive load
Cover frame colour tint	Lavender silver

Complementary

Wiring device mounting	Flush Surface
Outlet poles configuration	2P universal 2P + E china
Material	Polycarbonate with grid plate Polycarbonate with surround
Connections - terminals	Pillar terminals switch Clamp terminal socket
Clamping connection capacity	2 x 2.5 mm ² for solid cable(s)
Width	87 mm
Height	87 mm
Depth	8.8 mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	GB 2099.1-2008 GB 16915.1-2003

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1110 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------