



### Main

Range of product	Pieno
Product or component type	Power socket-outlet
Switch function	Switch
Rated current	10 A, 250 V, , AC, 50 Hz
Number of gangs	1 gang
Load type	No inductive load
Cover frame colour tint	Lavender silver

### Complementary

Wiring device mounting	Surface Flush
Outlet poles configuration	2P universal 2P + E china
Material	Polycarbonate with grid plate Polycarbonate with surround
Connections - terminals	Pillar terminals switch Clamp terminal socket
Clamping connection capacity	2 x 2.5 mm <sup>2</sup> for solid cable(s)
Width	87 mm
Height	87 mm
Depth	8.8 mm

### Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	GB 16915.1-2003 GB 2099.1-2008

E8215\_10US\_LS

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1110 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------