

Product data sheet

Characteristics

E8231BPDMW_LS

10A 250V 1G Bel SW w Illu Pvc, "Pls CleanUp" & "Pls Wait" Sym, Lavendar Silver



Main

Range of product	Pieno
Range	Pieno
Product or component type	Switch
Switch application	Control switch Bell switch
Load type	Fluorescent Resistive
Cover frame colour tint	White

Complementary

Wiring device mounting	Surface Flush
Device mounting	Surface Flush
Switch function	Switch
Rated current	10 A, 250 V, AC, 50 Hz
Local signalling	Please wait-neon with orange Please clean up-neon with green Privacy-neon with red
Material	Polycarbonate with grid plate Polycarbonate with surround
Connections - terminals	By screw
Clamping connection capacity	1 x 2.5 mm ² for solid cable(s) 1 x 1.5 mm ² for stranded cable(s)
Embedding depth	21 mm
Width	87 mm
Height	87 mm
Depth	35.5 mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	GB 16915.1 BS EN 60669-1

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1301 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------
