



### Main

Range of product	Pieno
Product or component type	Switch
Switch application	Bell
Load type	Resistive
Cover frame colour tint	White

### Complementary

Device mounting	Surface Flush
Wiring device mounting	Flush Surface
Switch function	Momentary
Rated current	10 A, 250 V, AC, 50 Hz
Local signalling	Fluorescent, white
Number of gangs	1 gang
Material	Polycarbonate with grid plate Polycarbonate with surround
Connections - terminals	Pillar terminals
Clamping connection capacity	2 x 2.5 mm <sup>2</sup> - cable stiffness: solid 2 x 1.5 mm <sup>2</sup> - cable stiffness: stranded
Embedding depth	23 mm
Width	87 mm
Height	87 mm
Depth	23 mm

### Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	BS EN 60669-1 SS 227-1 MS IEC 60669-1 GB 16915.1 IEC 60669-1

E8231BPL1\_WE

## Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1642 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>

## Contractual warranty

Warranty period	18 months
-----------------	-----------