



### Main

Range of product	Pieno
Product or component type	Switch
Switch application	Curtain switch
Load type	Fluorescent Resistive
Cover frame colour tint	Lavender silver

### Complementary

Device mounting	Flush Surface
Wiring device mounting	Surface Flush
Switch function	Switch
Rated current	10 A, 250 V, AC, 50 Hz
Local signalling	Fluorescent, white
Material	Polycarbonate with grid plate Polycarbonate with surround
Connections - terminals	Pillar terminals
Clamping connection capacity	2 x 1.5 mm <sup>2</sup> - cable stiffness: stranded 1 x 2.5 mm <sup>2</sup> - cable stiffness: solid
Embedding depth	22.6 mm
Width	87 mm
Height	87 mm
Depth	22.6 mm

### Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	IEC 60669-1 BS EN 60669-1 MS IEC 60669-1 GB 16915.1

E8231CF\_LS

Offer Sustainability

---

RoHS (date code: YYWW)	Compliant - since 1301 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>

---

Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---