

Product data sheet
Characteristics

E8231D20N_2_WE
20A 250V 1 Gang 2 Way Double Pole Switch with
Neon, White



Main

Range of product	Pieno
Product or component type	Switch
Switch application	Switch
Load type	Fluorescent Resistive
Cover frame colour tint	White

Complementary

Device mounting	Flush Surface
Wiring device mounting	Flush Surface
Switch function	2-way
Rated current	20 A, 250 V, AC, 50 Hz
Local signalling	Neon
Number of gangs	1 gang
Material	Polycarbonate with grid plate Polycarbonate with surround
Connections - terminals	Pillar terminals
Clamping connection capacity	3 x 2.5 mm ² - cable stiffness: solid 1 x 6 mm ² - cable stiffness: stranded
Embedding depth	23 mm
Width	87 mm
Height	87 mm
Depth	32.2 mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	BS EN 60669-1 GB 16915.1 IEC 60669-1 MS IEC 60669-1 SS 227-1

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Contractual warranty

Warranty period	18 months
-----------------	-----------
