



### Main

Range of product	Pieno
Product or component type	Switch
Switch application	Switch
Load type	Fluorescent Resistive
Cover frame colour tint	Lavender silver

### Complementary

Device mounting	Flush Surface
Wiring device mounting	Surface Flush
Rated current	45 A, 250 V, AC, 50 Hz
Local signalling	Neon
Number of gangs	1 gang
Material	Polycarbonate with grid plate Polycarbonate with surround
Connections - terminals	Pillar terminals
Clamping connection capacity	1 x 16 mm <sup>2</sup> - cable stiffness: solid 1 x 10 mm <sup>2</sup> - cable stiffness: stranded
Embedding depth	23 mm
Width	87 mm
Height	87 mm
Depth	33.8 mm

### Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	IEC 60669-1 MS IEC 60669-1 SS 227-1 BS EN 60669-1 GB 16915.1

E8231D45N\_LS

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Offer Sustainability

---

RoHS (date code: YYWW)	Compliant - since 1110 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>

---

Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---