



Main

Range of product	Pieno
Product or component type	Switch
Switch application	Switch
Load type	Fluorescent Resistive
Cover frame colour tint	Lavender silver

Complementary

Device mounting	Flush Surface
Wiring device mounting	Flush Surface
Rated current	20 A, 250 V, AC, 50 Hz
Local signalling	Neon
Number of gangs	2 gangs
Material	Polycarbonate with grid plate Polycarbonate with surround
Connections - terminals	Pillar terminals
Clamping connection capacity	3 x 2.5 mm ² - cable stiffness: solid 1 x 6 mm ² - cable stiffness: stranded
Embedding depth	23 mm
Width	87 mm
Height	87 mm
Depth	35.5 mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	BS EN 60669-1 GB 16915.1 IEC 60669-1 MS IEC 60669-1 SS 227-1

E8232D20N_LS

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1110 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------