

Product data sheet
Characteristics

E8232PRL1F_LS
10A 250V 2 Gang Momentary Switch with
Fluorescent Locator, Lavendar Silver



Main

Range of product	Pieno
Product or component type	Switch
Switch application	Switch
Load type	Resistive Fluorescent
Cover frame colour tint	Lavender silver

Complementary

Device mounting	Flush Surface
Wiring device mounting	Surface Flush
Switch function	Momentary
Rated current	10 A, 250 V, AC, 50 Hz
Local signalling	Fluorescent, white
Number of gangs	2 gangs
Material	Polycarbonate with grid plate Polycarbonate with surround
Connections - terminals	Pillar terminals
Clamping connection capacity	2 x 2.5 mm ² - cable stiffness: solid 2 x 1.5 mm ² - cable stiffness: stranded
Embedding depth	23 mm
Width	87 mm
Height	87 mm
Depth	23 mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	IEC 60669-1 GB 16915.1 SS 227-1 BS EN 60669-1 MS IEC 60669-1

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1110 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------
