Product data sheet Characteristics

E8232RD450U_LS

450W 240V 1 Gang Dimmer with Switch, Lavendar Silver



Range of product	Pieno	
Product or component type	Dimmer	
Power range	450 W LV halogen	
[Ue] rated operational voltage	250 V AC 50 Hz	
Number of gangs	1 gang	
Cover frame colour tint	Lavender silver	
Cover plate colour tint	Lavender silver	
Complementary		
Wiring device mounting	Flush Surface	
Connections - terminals	Pillar terminals	
Width	87 mm	
Height	87 mm	
Height Depth	87 mm 47 mm	
Depth Environment	47 mm	
Depth Environment Ambient air temperature for operation	47 mm -540 °C	
Depth Environment Ambient air temperature for operation Relative humidity Standards	47 mm -540 °C 095 %	
Environment Ambient air temperature for operation Relative humidity Standards Offer Sustainability	47 mm -540 °C 095 %	
Environment Ambient air temperature for operation Relative humidity Standards Offer Sustainability	47 mm -540 °C 095 % IEC 60669	
Depth Environment Ambient air temperature for operation Relative humidity Standards Offer Sustainability RoHS (date code: YYWW)	47 mm -540 °C 095 % IEC 60669 Compliant - since 1201 - Schneider Electric declaration of conformity	
Depth Environment Ambient air temperature for operation Relative humidity Standards Offer Sustainability RoHS (date code: YYWW)	47 mm -540 °C 095 % IEC 60669 Compliant - since 1201 - Schneider Electric declaration of conformity	
Environment Ambient air temperature for operation Relative humidity	47 mm -540 °C 095 % IEC 60669 Compliant - since 1201 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity Reference not containing SVHC above the threshold	
Depth Environment Ambient air temperature for operation Relative humidity Standards Offer Sustainability RoHS (date code: YYWW)	47 mm -540 °C 095 % IEC 60669 Compliant - since 1201 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold	

Complementary

Wiring device mounting Flush Surface Connections - terminals Pillar terminals	
Connections - terminals Pillar terminals	
Width 87 mm	
Height 87 mm	
Depth 47 mm	

Environment

Ambient air temperature for operation	-540 °C
Relative humidity	095 %
Standards	IEC 60669

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1201 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	7
	Reference not containing SVHC above the threshold	.s .g .g
Product environmental profile	Available	

Contractual warranty

Warranty period	18 months