



Main

| | |
|---------------------------|--------------------------|
| Range of product | Pieno |
| Product or component type | Switch |
| Switch application | Switch |
| Load type | Resistive Fluorescent |
| Cover frame colour tint | Lavender silver |

Complementary

| | |
|------------------------------|---|
| Device mounting | Surface Flush |
| Wiring device mounting | Flush Surface |
| Switch function | 2-way |
| Rated current | 10 AX, 250 V, AC, 50 Hz |
| Local signalling | Fluorescent, white |
| Number of gangs | 4 gangs |
| Material | Polycarbonate with grid plate Polycarbonate with surround |
| Connections - terminals | Pillar terminals |
| Clamping connection capacity | 2 x 2.5 mm ² - cable stiffness: solid 2 x 1.5 mm ² - cable stiffness: stranded |
| Embedding depth | 23 mm |
| Width | 87 mm |
| Height | 87 mm |
| Depth | 23 mm |

Environment

| | |
|---------------------------------------|--|
| Ambient air temperature for operation | -5...40 °C |
| Relative humidity | 0...95 % |
| Standards | GB 16915.1 BS EN 60669-1 SS 227-1 IEC 60669-1 MS IEC 60669-1 |

Offer Sustainability

| | |
|------------------------|---|
| RoHS (date code: YYWW) | Compliant - since 1110 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|
