



### Main

Range	Multi 9
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Lines description	1L
Total number of 18 mm modules	6

### Complementary

Number of ways	6 ways 1 L
Poles configuration for 1 way	1 x 1P
Connection pitch	18 mm
Connector type	Tooth
Distance between way	18 mm
Insulation	Insulated
Device presentation	Uncuttable
[Ie] rated operational current	115 A ( 40 °C )
[Ue] rated operational voltage	480 V AC 50/60 Hz Ph/Ph 277 V AC 50/60 Hz Ph/N
[Ui] rated insulation voltage	1000 V AC 50/60 Hz conforming to UL 508
Mounting mode	Horizontal
Mounting location	Top on tunnel type terminals
9 mm pitches	12
Width	108 mm
Colour	Light grey ( RAL 7035 )
Range compatibility	Multi 9 C60BP

### Environment

Standards	UL 508
Fire resistance	960 °C ( 30 s ) conforming to IEC 60695-2-1
Pollution degree	3
IP degree of protection	IP20 with end-pieces and tooth covers

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Offer Sustainability

---

RoHS (date code: YYWW)	Compliant - since 1736 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>

---