



Main

Range of product	Lexium MAX H
Product or component type	Double portal axis
Product specific application	For 1 direction
Load position	On 2 parallel carriages
Drive type	Toothed belt on 1 axis
Guide type	Roller

Complementary

Operating position	Horizontal by combination of 2 parallel axis X and X
Kit composition	PAS 4*B axis PAS 4*H support axis driven by the load
Function available	Different types of sensors for the limit switch function Different types of carriage adapted to the load 1 to 3 carriages Anti-corrosion version proof enhance Anti-static belt Protective metal strip Different types of motor mounting Variable distance between the 2 axis
Operating force	≤ 300 N for F_x ≤ 990 N for F_y ≤ 645 N for F_z
Maximum actuation speed	8 m/s
Acceleration	≤ 20 m/s ²
Drive torque	≤ 4 N.m
Torque value	≤ 17 N.m for M_z (carriage type 2) ≤ 43 N.m for M_z (carriage type 4) ≤ 56 N.m for M_y (carriage type 4) ≤ 35 N.m for M_x ≤ 22 N.m for M_y (carriage type 2)
Operating travel	125...3000 mm
Distance between axis	100...300 mm
Repeat accuracy	+/- 0.1 mm
Outer dimension	40 x 40 mm
Mechanical service life	30000 km

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications