



Overview

Description	A pre-assembled Micro Data Center includes: shock packaged rack, two UPS, two switched rack PDUs, NetBotz 250 with rack access handles, one temperature/humidity probe, blanking panels, and brush strip.
Model Name	Micro DC 24U SX, 3KVA, 230V
Standard Lead Time	Usually in Stock
Product Distribution	Andorra , Armenia , Austria , Azerbaijan , Belarus , Belgium , Bosnia And Herzegovina , Bulgaria , Croatia , Cyprus , Czech Republic , Denmark , Estonia , Finland , France , Georgia , Germany , Greece , Hungary , Iceland , Ireland , Israel , Italy , Kazakhstan , Latvia , Liechtenstein , Lithuania , Luxembourg , Macedonia , Malta , Moldova, Republic Of , Netherlands , Norway , Poland , Portugal , Romania , Russian Federation , Slovakia (Slovak Republic) , Slovenia , Spain , Sweden , Switzerland , Ukraine , Uzbekistan

Supported Hardware

Panel Size	0
Brightness	0 nits
Pixel Pitch	0.0
Display Colors	0
LCD Power Consumption	0 W

Physical

Net Weight	179.17 kg
Maximum Height	1199.0 mm
Maximum Width	600.0 mm
Maximum Depth	1070.0 mm
Shipping Weight	247.21 kg
Shipping Height	1350.0 mm
Shipping Width	899.0 mm
Shipping Depth	1219.0 mm
Minimum Mounting Depth	7.52
Maximum Mounting Depth	36.02
Rack Height	24 U
Units per Pallet	0.0
Vertical Posts	16 gauge

Front Door	16 gauge
Rear Door	18 gauge
Roof	18 gauge
EIA Mounting Rails	14 gauge
Side Panels	18 gauge

Environmental

CFM	0
-----	---