



## Main

Range	PowerLogic
Range of product	PowerLogic CT
Product name	CT
Product or component type	Current transformer
Secondary current	5 A
Accuracy class	Class 0.5 maximum power: 4 VA Class 1 maximum power: 6 VA
[In] rated current	300 A

## Complementary

Current transformer type	Tropicalised for busbar and cable
Current transformer ratio	300/5
[Ith] conventional free air thermal current	18 kA
Dynamic withstand current	2.5 Ith
Safety factor	<= 5
[Ue] rated operational voltage	< 720 V AC at 50/60 Hz
[Ui] rated insulation voltage	3 kV
Mounting mode	By screws Insulated locking screw Clip-on
Mounting support	DIN rail Mounting plate Busbar
Width	60 mm outside
Height	85 mm outside
Depth	43 mm outside
Diameter	26 mm
Product weight	0.323 kg

METSECT5MB030

[Uimp] rated impulse withstand voltage	3 kV
Electrical insulation class	Class B
Opening of bars	40.5 x 12.5 32.5 x 15.5
Cable outer diameter	26 mm max
Sealing	Without
Compatibility code	MB

## Environment

Standards	IEC 61869-2 VDE 0414
Product certifications	CE
IP degree of protection	IP20
Relative humidity	0...95 %
Ambient air temperature for operation	-25...60 °C

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1427 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations