



Main

Range	EasyLogic
Product name	EasyLogic DM6X00H NC
Device short name	DM6000H
Product or component type	VAF PF meter

Complementary

Device application	Remote monitoring
Type of measurement	RPM Voltage Current Frequency
Metering type	Frequency Phase currents Rotation speed Voltage U21, U32, U13, V1, V2, V3 Average voltage Vavg Average current Iavg Unbalance current Unbalance voltage Calculated neutral current
Counter functions	ON hour counting Power interruption
[Us] rated supply voltage	48...277 V AC 45...65 Hz 48...277 V DC
Network frequency	50 Hz 60 Hz
[In] rated current	1 A 5 A
Poles description	1P + N 2P 2P + N 3P 3P + N

METSEDM6000HCL10NC

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Power consumption in VA	4 VA at 240 V AC between phase and neutral
Power consumption in W	2 W at 240 V DC
Display type	8 segments LED
Display colour	Red
Messages display capacity	3 fields of 4 characters
Display digits	12 digit(s) - 14.2 mm in height
Communication of data	Instantaneous and demand values Reading of measurements All counters Revolution speed
Tamperproof of settings	Protected by access code
Sampling rate	32 samples/cycle
Measurement current	5...6000 mA
Analogue input type	Current 0.005...10 A (impedance 0.3 MOhm) 6 terminal(s)
Measurement voltage	35...480 V AC 50...60 Hz between phases 46...277 V AC 50...60 Hz between phase and neutral 277...999000 V AC 50...60 Hz with external VT
Frequency measurement range	45...65 Hz
Measurement accuracy	+/- 0.05 % frequency +/- 0.01 power factor +/- 1 % current +/- 1 % voltage
Accuracy class	Class 1
Refresh time	1 s
Local signalling	Green LED : activity Red LED : output signal
Communication port protocol	-
Material	Polycarbonate
Flame retardance	V-0 UL 94 conforming to UL 94 V-0
Mounting mode	Flush-mounted
Mounting support	Framework
Installation category	III
Type of installation	Indoor installation
Measurement category	Category III up to <= 480 V
Electrical insulation class	Class II
Connections - terminals	Current circuit : bottom screw clamp terminals 2.08...3.31 mm ² Voltage circuit : top screw clamp terminals 0.82...3.31 mm ² Control circuit : top screw clamp terminals 0.82...3.31 mm ²
Tightening torque	Current circuit : 0.9...1 N.m with Philips No 2 Voltage circuit : 0.9...1 N.m with Philips No 2 Control circuit : 0.9...1 N.m with Philips No 2
Wire stripping length	Current circuit : 3.68 mm Voltage circuit : 7 mm Control circuit : 7 mm
Standards	IEC 61010-1 ed. 3 UL 61010-1 ed. 3
Product certifications	CE conforming to IEC 61010-1 CULus conforming to UL 61010-1 CULus conforming to CSA C22.2 No 61010-1 C-Tick
Width	96 mm
Depth	13 mm outside 49 mm panel
Height	96 mm
Product weight	300 g

Environment

Electromagnetic compatibility	<ul style="list-style-type: none"> • electrical fast transient/burst immunity test, conforming to IEC 61000-4-4 • conducted RF disturbances, conforming to IEC 61000-4-6
-------------------------------	--

- radiated radio-frequency electromagnetic field immunity test, conforming to IEC 61000-4-3
- voltage dips and interruptions immunity test, conforming to IEC 61000-4-11
- electrostatic discharge, conforming to IEC 61000-4-2
- surge immunity test, conforming to IEC 61000-4-5
- magnetic field at power frequency, conforming to IEC 61000-4-8
- emission tests, conforming to FCC part 15 class A
- emission tests, conforming to FCC part 15 subpart C
- emission tests, conforming to FCC part 15 subpart E

Overvoltage category	III
IP degree of protection	IP30 (body) conforming to IEC 60529 IP51 (front) conforming to IEC 60529
Relative humidity	5...95 % 50 °C
Pollution degree	2
Ambient air temperature for operation	-10...60 °C
Ambient air temperature for storage	-20...70 °C
Operating altitude	<= 2000 m
Service life	> 7 yr
Targeted country	All

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1730 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available

METSEDM6000HCL10NC