

METSEPM5560

PM5560 powermeter w 1mod2eth - upto 63th H -
1,1M 4DI/2DO 52alarms - flush mount



Main

Range	PowerLogic
Product name	PowerLogic PM5000
Device short name	PM5560
Product or component type	Power meter
Market segment	Buildings / Multi-site (Energy Cost management) for Main incomer in Billing Datacenter (Energy Cost management) for Sub feeder in Billing Industry (Energy Cost management) for Main incomer in Billing Buildings / Small building (Energy Cost management) for Sub feeder in Cost allocation Buildings / Large building (Energy Cost management) for Sub feeder in Cost allocation Datacenter (Energy Cost management) for Main incomer in Cost allocation Healthcare (Energy Cost management) for Sub feeder in Cost allocation Buildings / Small building (Energy Network management) Main incomer in Healthcare (Energy Network management) Sub feeder in Buildings / Medium building (Energy Cost management) for Main incomer in Billing Buildings / Large building (Energy Cost management) for Sub feeder in Billing Datacenter (Energy Cost management) for Main incomer in Billing Healthcare (Energy Cost management) for Sub feeder in Billing Buildings / Large building (Energy Cost management) for Main incomer in Cost allocation Buildings / Multi-site (Energy Cost management) for Sub feeder in Cost allocation Healthcare (Energy Cost management) for Main incomer in Cost allocation Buildings / Medium building (Energy Network management) Sub feeder in Datacenter (Energy Network management) Sub feeder in Buildings / Small building (Energy Cost management) for Main incomer in Billing Buildings / Medium building (Energy Cost management) for Sub feeder in Billing Healthcare (Energy Cost management) for Main incomer in Billing Industry (Energy Cost management) for Sub feeder in Billing Buildings / Medium building (Energy Cost management) for Main incomer in Cost allocation Datacenter (Energy Cost management) for Sub feeder in Cost allocation Industry (Energy Cost management) for Main incomer in Cost allocation Buildings / Small building (Energy Network management) Sub feeder in Buildings / Large building (Energy Network management) Sub feeder in Buildings / Small building (Energy Cost management) for Sub feeder in Billing Buildings / Large building (Energy Cost management) for Main incomer in Billing Buildings / Multi-site (Energy Cost management) for Sub feeder in Billing Buildings / Small building (Energy Cost management) for Main incomer in Cost allocation Buildings / Medium building (Energy Cost management) for Sub feeder in Cost allocation Buildings / Multi-site (Energy Cost management) for Main incomer in Cost allocation Industry (Energy Cost management) for Sub feeder in Cost allocation

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Complementary

Power quality analysis	Up to the 63rd harmonic
Device application	WAGES metering Gateway Multi-tariff Power monitoring
Type of measurement	Energy Active and reactive power Voltage Current Frequency Power factor
[Us] rated supply voltage	125...250 V DC 100...480 V AC (45...65 Hz)
Network frequency	50 Hz 60 Hz
[In] rated current	1 A 5 A
Poles description	3P + N 3P 1P + N
Power consumption in VA	10 VA at 480 V
Display type	Backlit LCD
Display resolution	128 x 128 pixels
Sampling rate	128 samples/cycle
Measurement current	5...10000 mA
Analogue input type	Current (impedance 0.3 mOhm) Voltage (impedance 5 MOhm)
Measurement voltage	20...400 V AC 45...65 Hz between phase and neutral 20...690 V AC 45...65 Hz between phases
Frequency measurement range	45...65 Hz
Number of inputs	4 digital
Measurement accuracy	+/- 0.5 % apparent power +/- 0.05 % frequency +/- 0.2 % active energy +/- 1 % reactive energy +/- 0.2 % active power +/- 0.1 % voltage +/- 0.05 % power factor +/- 0.15 °C current
Accuracy class	Class 0.2S (active energy according to IEC 62053-22)
Number of outputs	2 digital
Information displayed	Tariff 8
Communication port protocol	Modbus RTU and ASCII 2 wires, : 9.6, 19.2 and 38.4 kbauds, even/odd or none, insulation: 2500 V JBUS Modbus TCP/IP : 10/100 Mbit/s, insulation: 2500 V Ethernet Modbus TCP/IP daisy chain BACnet IP
Communication port support	RS485 Ethernet
Communication gateway	Ethernet/Serial
Data recording	Data logs Alarm logs Time stamping Min/Max of instantaneous values Maintenance logs Event logs
Memory capacity	1.1 MB
Web services	Web server

	Diagnostic via predefined web pages Alarm notification by e-mail Real time viewing of data
Ethernet service	SNMP-Traps SNTP client
Connections - terminals	Voltage circuit: 4 screw terminal block Control circuit: 2 screw terminal block Current transformer: 6 screw terminal block RS485 link: 4 screw terminal block Digital input: 8 screw terminal block Digital output: 4 screw terminal block Ethernet network: 2 RJ45 connector
Mounting mode	Flush-mounted
Mounting support	Framework
Standards	EN 50470-3 UL 61010-1 IEC 61557-12 IEC 62053-22 IEC 62053-24 IEC 60529 EN 50470-1
Product certifications	CE conforming to IEC 61010-1 CULus conforming to UL 61010-1 BTL
Width	96 mm
Depth	72 mm
Height	96 mm
Product weight	450 g

Environment

Electromagnetic compatibility	<ul style="list-style-type: none"> • conducted and radiated emissions class class B, conforming to EN 55022 • limitation of voltage changes, voltage fluctuations and flicker in low-voltage, conforming to IEC 61000-3-3 • limits for harmonic current emissions class class A, conforming to IEC 61000-3-2 • conducted RF disturbances class level 3, conforming to IEC 61000-4-6 • magnetic field at power frequency class level 4, conforming to IEC 61000-4-8 • electrostatic discharge class level 4 (8 kV), conforming to IEC 61000-4-2 • radiated radio-frequency electromagnetic field immunity test, conforming to IEC 61000-4-3 • electrical fast transient/burst immunity test class level 4, conforming to IEC 61000-4-4 • surge immunity test class level 4, conforming to IEC 61000-4-5 • voltage dips and interruptions immunity test, conforming to IEC 61000-4-11
IP degree of protection	IP52 (front) conforming to IEC 60529 IP30 (body) conforming to IEC 60529
Relative humidity	5...95 % 50 °C
Pollution degree	2
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...85 °C
Operating altitude	3000 m

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1340 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Available End of life manual