



### Main

Range	PowerLogic
Product or component type	Remote display
Device application	Human-machine dialogue application
Range compatibility	Powerlogic PowerLogic PM8000 Powerlogic PowerLogic ION7400
Display type	Colour TFT LCD

### Complementary

Display resolution	320 x 240 pixels QVGA
Information displayed	Energy consumption Harmonic distortion I/O status Voltage Power Current System alarm Frequency
Messages display capacity	Graphic objects ( bargraph, button, light...)
Local signalling	Status : green LED Alarm : red LED
Control type	5 x push-button
Connector type	RJ45
Provided equipment	Mounting hardware 3 m cable
Mounting mode	Flush-mounted
Mounting support	Remote display on framework
Width	96 mm
Height	96 mm
Projecting depth	27 mm
Product weight	300 g

### Environment

IP degree of protection	IP54 according to IEC 60529
Relative humidity	5...95 %

Operating altitude	0...3000 m
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...85 °C
Product certifications	IEC

## Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1425 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
------------------------	---