



Overview

Model Name	Phase Module, 120/208V, 160KA, for Modular Panels
Includes	User Manual
Standard Lead Time	Usually Ships within 3 Weeks
Product Distribution	Canada , United States

Output

Number of Outlets	0
-------------------	---

Input

Nominal Input Voltage	208 3PH
Input Power	0 W
Maximum Line Current per phase	0.0 A
Maximum Input Current	0 A

Surge Protection and Filtering

EMI/RFI Noise rejection (100 kHz to 10 MHz)	30.0 dB
Peak Current Normal Mode	160 (/PH) kA
Peak Current Common Mode	160.0 kA
NM Surge Response Time (ns)	1.0 NS
Let Through Voltage Rating	400

Physical

Net Weight	0.91 kg
Maximum Height	114.0 mm
Maximum Width	83.0 mm
Maximum Depth	71.0 mm
Shipping Weight	1.14 kg
Shipping Height	213.0 mm
Shipping Width	137.0 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Shipping Depth	108.0 mm
Master Carton Units	0.0
Master Carton Weight	0.0 lbs
SCC Codes	1073130426656 0
Units per Pallet	0.0

Conformance

Approvals	UL 1283 , UL 1449 , cUL Listed
Standard warranty	10 years repair or replace
UL 1449 TVSS Rating	<400