



### Main

Range of product	Unica
Range	Unica
Aesthetic name	Unica (standard aesthetic)
Product or component type	TV/FM socket
Device presentation	Complete mechanism
TV socket type	Individual socket
Colour tint	White

### Complementary

TV connector	Male IEC 9.52 mm
Radio connector	Female IEC 9.52 mm
Path attenuation	TV/UHF : < 1 dB @125...860 MHz TV/VHF : 2 dB @47...68 MHz R : 10 dB @87.5...108 MHz
DC current flow	No
Number per line	1
Number of modules	2 modules
Material	Cover frame : ABS (acrylonitrile butadiene-styrene) Mechanism cover : ASA + PC Fixing frame : PBT (polybutylene terephthalate) GF30
Condition of use	Parallel distribution systems
Fixing mode	Short claws
Depth	28 mm
Width	37 mm
Height	85 mm
Embedding depth	18 mm
Product weight	0.1065 kg

MGU10.451

## Environment

IP degree of protection	IP20
IK degree of protection	IK01
Ambient air temperature for operation	15...35 °C
Ambient air temperature for storage	0...35 °C
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free
Standards	EMC directive EN 50083-1 EN 50083-2 EN 50083-4

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0702 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------