



Main

Range of product	Unica
Range	Unica
Aesthetic name	Unica (standard aesthetic)
Product or component type	TV/FM socket
Device presentation	Complete mechanism
TV socket type	End-of-line (terminal socket)
Colour tint	White

Complementary

TV connector	Male IEC 9.52 mm
Radio connector	Female IEC 9.52 mm
Path attenuation	TV/UHF : 13.5 dB @125...860 MHz TV/VHF : 13.5 dB @47...68 MHz R : 27 dB @87.5...108 MHz
DC current flow	Yes
Number per line	1
Number of modules	2 modules
Material	Cover frame : ABS (acrylonitrile butadiene-styrene) Mechanism cover : ASA + PC Fixing frame : PBT (polybutylene terephthalate) GF30
Condition of use	Series distribution systems
Fixing mode	Short claws
Depth	28 mm
Width	85 mm
Height	80 mm
Embedding depth	18 mm
Product weight	0.106 kg

Environment

IP degree of protection	IP20
IK degree of protection	IK01
Ambient air temperature for operation	15...35 °C

Ambient air temperature for storage	0...35 °C
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free
Standards	EMC directive EN 50083-1 EN 50083-2 EN 50083-4

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0702 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------