



Main

Range	Unica
Range of product	Unica
Aesthetic name	Unica (standard aesthetic)
Product or component type	Telephone socket
Device presentation	Complete mechanism
Colour tint	White
Telephone socket type	RJ11 (4 contacts): cat.3 (rate: 16 Mbit/s)

Complementary

Socket number	1
Number of modules	2 modules
Connections - terminals	Screw terminals (twisted pair)
Fixing mode	Long claws
Material	Mechanism cover : ASA + PC Cover frame : ASA + PC Fixing frame : PBT (polybutylene terephthalate) GF30
Depth	23 mm
Width	85 mm
Height	80 mm
Embedding depth	12 mm
Product weight	0.05 kg
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C

Environment

IP degree of protection	IP20
IK degree of protection	IK01
Environmental characteristic	Petrol

MGU10.492

Acetone
Ammonia
Window-cleaning fluid
Liquid soap
UV resistant
Alcohol
Oil
Bleach

Environmental health and issues	Halogen free
---------------------------------	--------------

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0803 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------
