



Main

Range of product	Unica
Aesthetic name	Unica (standard aesthetic)
Aesthetic cover frame name	Unica Basic
Product or component type	Rotary dimmer
Device presentation	Complete mechanism
Fixing mode	Short claws
Dimmer application	Inductive load Resistive load
[Ue] rated operational voltage	230 V AC, 50 Hz
Number of modules	2 modules
Cover plate colour tint	White
Cover frame colour tint	White

Complementary

Dimmer control	270° rotary setting ON/OFF push
Maximum permanent current	1.74 A
Total number of wires	2
Load type	230 V AC halogen lamp - 40...400 W 230 V AC incandescent lamp - 40...400 W Low voltage halogen lamp with ferromagnetic transformer - 40...400 VA Low voltage halogen lamp with electronic transformer - 40...400 VA
Protection type	Fuse protection
Fuse type	4 Ah (5 x 20 mm) @230 V 50 Hz
Marking	L+N
Connections - terminals	Screw terminals
Clamping connection capacity	<= 2 x 2.5 mm ² for flexible cable(s) <= 2 x 2.5 mm ² for rigid cable(s)
Connected auxiliaries	2-way switch
Material	Cover frame : ABS (acrylonitrile butadiene-styrene) Mechanism cover : ASA + PC Fixing frame : PBT GF30
Standards	EN 60669-2-1
Product certifications	CE

Ambient air temperature for operation	5...30 °C
Ambient air temperature for storage	-20...60 °C
Embedding depth	34 mm
Depth	54 mm
Width	85 mm
Height	80 mm
Product weight	0.1045 kg

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free

Contractual warranty

Warranty period	18 months
-----------------	-----------