



Main

Range of product	Unica
Range	Unica
Device application	Mounting
Product or component type	Mounting box
Aesthetic name	Unica (standard aesthetic)
Product compatibility	Except stand alone electronics
Device presentation	Assembly
Number of modules	4 modules
Number of gangs	2 gangs
Fixing mode	Pins
Colour tint	White

Complementary

Provided equipment	Cover frame
Device mounting	Surface
Cable entry	5 knock-outs
Fire resistance	650 °C @30 s
Material	Cover frame : ASA + PC Box : ASA + PC Fixing frame : PBT (polybutylene terephthalate)
Standards	UNE 60670-1
Depth	36 mm
Width	125 mm
Height	65 mm
Product weight	0.0961 kg

MGU22.304

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0803 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------