



Main

Range	Unica
Range of product	Unica
Device application	Power supply
Product or component type	Socket-outlet
Aesthetic name	Unica (standard aesthetic)
Device presentation	Complete mechanism
Socket number	2
Outlet poles configuration	2P + E
Outlet standard	German
Socket additional information	Side earth
Outlet standard description	Side earth

Complementary

Rated current	16 A, 250 V AC
Network frequency	50/60 Hz
Number of modules	2 modules
Fixing mode	Long claws
Colour tint	White
Connections - terminals	Screw terminals
Cable cross section	0...4 mm ² - cable stiffness: flexible 0...4 mm ² - cable stiffness: rigid
Minimum load breaking capacity	100 operations 1.25 In and 1.1 Un, cos phi: 0.6
Electrical durability	10000 cycles (cos phi: 0.8)
Insulation resistance	> 5 MOhm @500 V
Dielectric strength	2000 V
Material	Cover frame : ABS (acrylonitrile butadiene-styrene) Mechanism cover : ASA + PC Fixing frame : PBT (polybutylene terephthalate) GF30
Quantity per set	Blister : set of 1
Embedding depth	30 mm
Depth	40 mm
Width	85 mm

Height	80 mm
--------	-------

Environment

Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Bleach Petrol Oil Ammonia Acetone UV resistant Alcohol Liquid soap Window-cleaning fluid
Environmental health and issues	Halogen free

Contractual warranty

Warranty period	18 months
-----------------	-----------
