



Main

Range of product	Unica
Range	Unica
Device application	Power supply
Product or component type	1 socket-outlet
Aesthetic name	Unica
Device presentation	Complete socket-outlet
Outlet poles configuration	2P + E with shutters
Outlet standard	Euroamerican
Socket additional information	Earthed
Decoration colour	White RAL 9003
Cover plate colour tint	White RAL 9003
Cover frame colour tint	White RAL 9003
Quantity per set	Set of 1 blister

Complementary

Rated current	15 A 127 V AC 50/60 Hz 10 A 250 V AC 50/60 Hz
Number of modules	1 module
Fixing mode	Clip-in
Connections - terminals	Screw terminals
Cable cross section	<= 4 mm ² flexible cable <= 4 mm ² rigid cable
Minimum load breaking capacity	100 operations 1.25 I _n and 1.1 I _n , cos φ = 0.6
Electrical durability	10000 cycles, cos φ = 0.8
Insulation resistance	>= 5 MOhm / 500 V
Material	Mechanism cover : ASA + PC
Embedding depth	21 mm
Depth	33 mm

Width	22.5 mm
Height	45 mm
Product weight	0.024 kg
Surface treatment	Untreated

Environment

Dielectric strength	>= 2000 V
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
IK degree of protection	IK01
IP degree of protection	IP20
Standards	IEC 60884-1
Environmental characteristic	Ammonia Acetone Liquid soap Petrol UV resistant Bleach Alcohol Window-cleaning fluid Oil

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1101 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------