



### Main

Range of product	Unica
Range	Unica
Aesthetic name	Unica Top - Unica Class
Device application	Control
Product or component type	Switch
Device presentation	Mechanism
Switch function	1-pole 1-way
Colour tint	Graphite

### Complementary

Rated current	10 A, 250 V AC, 50/60 Hz
Electrical durability	40000 cycles (cos phi: 0.6)
Insulation resistance	> 5 MOhm @500 V
Dielectric strength	2000 V
Minimum load breaking capacity	200 operations 1.25 In and 1.1 Un, cos phi: 0.3
Condition of use	Impulse relay control
Opening distance	> 3 mm
Actuator	Push-button
Number of modules	1 module
Connections - terminals	Screw terminals
Cable cross section	0...2.5 mm <sup>2</sup> (rigid) 0...2.5 mm <sup>2</sup> (flexible)
Material	Mechanism cover : ABS (acrylonitrile butadiene-styrene)
Fixing mode	Clip-in
Width	22.5 mm
Height	45 mm
Depth	33 mm

MGU3.106T

Embedding depth	21 mm
Product weight	0.019 kg
Ambient air temperature for operation	25...35 °C
Ambient air temperature for storage	0...50 °C
Standards	EMC directive LV directive EN 60669-1

## Environment

IP degree of protection	IP20
IK degree of protection	IK01
Environmental characteristic	UV resistant Alcohol Ammonia Acetone Oil Liquid soap Window-cleaning fluid Petrol Bleach
Environmental health and issues	Halogen free

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0622 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------