



Main

Range of product	Unica
Range	Unica
Device application	Control
Product or component type	Switch
Aesthetic name	Unica Top - Unica Class
Device presentation	Mechanism
Switch function	Double 2-way
Switch application	Roller blind
Rated current	10 AX, 250 V AC, 50/60 Hz
Actuator	Rocker
Number of modules	1 module
Fixing mode	Clip-in
Cover plate colour tint	Graphite

Complementary

Contacts type and composition	1 C/O + 1 C/O
Mechanical interlocking	Interlock between up/down
[I _u] rated interrupted current	Motor : 2.5 A
Opening distance	> 3 mm
Marking	UP Down
Connections - terminals	Screw terminals
Cable cross section	<= 2.5 mm ² (flexible) <= 2.5 mm ² (rigid)
Minimum load breaking capacity	200 operations 1.25 I _n and 1.1 U _n , cos phi: 0.3
Electrical durability	40000 cycles (cos phi: 0.6)
Insulation resistance	> 5 MOhm @500 V
Dielectric strength	> 2000 V

Material	Mechanism cover : ASA + PC
Standards	EMC directive EN 60669-1 LV directive
Ambient air temperature for operation	25...35 °C
Ambient air temperature for storage	0...50 °C
Embedding depth	21 mm
Depth	33 mm

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Petrol Oil Acetone UV resistant Bleach Window-cleaning fluid Ammonia Alcohol Liquid soap
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0852 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------